PRICING. PERFORMANCE. OPTIONS.

132

12221

THE MIND OF AN ENGINEER. THE HEART OF A PILOT.



CIRRUS AIRCRAFT MODELS BETTER, BEST

SRV PRICES

The CIRRUS SRV offers a standard [VFR-only] all-glass Primary Flight Display [PFD]. The pilot-friendly avionics system provides navigational accuracy and communications efficiency BETTER than any other VFR-only aircraft in its class.

STANDARD	BASE PRICE \$189,900
CIRRUS AIRFRAME PARACHUTE™ magnetic compass annunciator panel engine instruments single alt/dual battery all electrical systems	2 blade propeller fabric interior visors bolster switches eyeball air vents backup instruments

Avidyne Entegra Primary Flight Display [PFD] for VFR Avidyne FlightMax[®] EX3000C Multi-Function Display [MFD] Garmin Avionics

GMA 340 Audio Panel GNC 420 GPS/COM GTX 327 Transponder

SRV OPTIONS	WEIGHT	COST
Avidyne EX5000C	1	\$2,950
WX-500 Stormscope®*	8	\$9,500
Skywatch [®] Traffic Information	13	\$21,500
Emax Engine & Fuel Monitoring	7	\$5,750
dual alternator system upgrade	7	\$2,400
nose wheel pant and fairing	3	\$1,550
3 blade propeller	23	\$3,000
HID landing light	5	\$900
extended third year warranty	_	\$4,995
LX INTERIOR PACKAGE leather interior, noise cancelling ja rear reading lights, rear cup holde courtesy power jack	,	\$3,900
CROSS COUNTRY PACKAGE VFR PFD upgrade, EX5000C, GNS 430, autopilot 55SR	10	\$15,800
TOURING PACKAGE		
VFR PFD upgrade, GNS 430, autopilot 55SR, dual alternator, nose wheel pant and fairing, LX ir	25 storior HID	\$17,400
* only available with EX5000C upgrade	iterioi, i liD	ianung ngm

sr20 PRICES

The CIRRUS SR20 features the BEST price-to-performance ratio in its class. The 200-horsepower engine burns only 10.5 gallons per hour, has a maximum range of 882 nautical miles and a 930-pound useful load.

STANDARD BASE PRICE \$229.700 2 blade propeller CIRRUS AIRFRAME PARACHUTE™ fabric interior magnetic compass annunciator panel visors engine instruments bolster switches dual alternator/dual battery eveball air vents noise cancelling pwr jacks all electrical systems HID landing light backup instruments

Avidyne Entegra Primary Flight Display [PFD]

Avidyne FlightMax® EX3000C Multi-Function Display [MFD] Garmin Avionics

GMA 340 Audio Panel GNS 430 Color GPS/COM/NAV GNC 250XL GPS/COM [back-up VFR GPS] GTX 327 Transponder Autopilot 55SR

SR20 OPTIONS	WEIGHT	COST
Avidyne EX5000C	1	\$2,950
WX-500 Stormscope®*	8	\$9,500
Skywatch [®] Traffic Information*	13	\$21,500
Emax Engine & Fuel Monitoring	7	\$5,750
GNS 430/420, autopilot 55SR [from t	base aircraft] -	\$4,245
GNS 430/430, autopilot 55X [from bas	e aircraft] -	\$17,845
3 blade propeller	23	\$3,000
leather interior	9	\$3,300
extended third year warranty • only available with EX5000C upgrade	-	\$4,995



sr22 PRICES

The CIRRUS SR22 offers pure aviation excitement. The 310horsepower engine produces 1,000 feet per minute climb rate through 12,000 feet, allowing you to soar farther and higher. BRILLIANT in every respect, SR22 speed and range in excess of 1,000 nautical miles unlocks the full potential of personal aviation.

STANDARD	BASE PRICE \$313,900
CIRRUS AIRFRAME PARACHUTE™	3 blade propeller
magnetic compass	leather or fabric interior
annunciator panel	visors
engine instruments	bolster switches
dual alternator/dual battery	eyeball air vents
all electrical systems	noise cancelling pwr jacks
backup instruments	electric attitude indicator
HID landing light	

Avidyne Entegra Primary Flight Display [PFD] Avidyne FlightMax[®] EX5000C Multi-Function Display [MFD] Garmin Avionics GMA 340 Audio Panel GNS 430 Color GPS/COM/NAV GNC 420 Color GPS/COM GTX 327 Transponder Autopilot 55SR

SR22 OPTIONS	WEIGHT	COST
GNS 430, 430, autopilot 55X	_	\$13,600
WX-500 Stormscope [®]	8	\$9,500
Skywatch [®] Traffic Information	13	\$21,500
Emax Engine & Fuel Monitoring	7	\$5,750
Ice Protection	30	\$19,700
extended third year warranty	-	\$4,995

At CIRRUS, we take pride introducing general aviation to the innovation and technology of the future. Our latest milestone is our all glass cockpit as standard equipment.

Our glass cockpit features two 10-inch displays. The PFD includes an electronic attitude director indicator [EADI], electronic horizontal situation indicator [EHSI], altimeter, airspeed indicator, vertical speed indicator. The multi-function display [MFD] is a moving map that supports lightning and traffic information. You'll wonder how you ever flew without it.

AND... BRILLIANT

CIRRUS SPECIFICATIONS


PERFORMANCE	SRV	sr 20	sr 22
takeoff	1341 ft	1341 ft	1020 ft
takeoff [50' object]	1958 ft	1958 ft	1575 ft
climb rate	900 ft/min	900 ft/min	1400 ft/min
stall speed with flaps	54 KIAS	54 KIAS	59 KIAS
cruise speed [8000 ft] 75% power	150 KTAS	156 KTAS	180 KTAS
cruise range with reserve	634 nm	733 nm	700 nm
maximum range	865 nm	882 nm	over 1000 nm
landing ground roll	1014 ft	1014 ft	1140 ft
landing over 50' object	2040 ft	2040 ft	2325 ft
ENGINE			
manufacturer	CONTINENTAL	CONTINENTAL	CONTINENTAL
model	IO-360-ES / 200hp	IO-360-ES / 200hp	IO-550-N / 310hp
PROPELLER			
diameter	76"	76"	78"
description	2 blade	2 blade	3 blade
	constant speed	constant speed	constant speed
SPECIFICATIONS			
length	26'	26'	26'
height	8' 6"	8' 6"	8' 7"
wingspan	35' 7"	35' 7"	38' 6"
wing area	135 sq ft	135 sq ft	144.9 sq ft
cabin length	130"	130"	130"
cabin width	49"	49"	49"
cabin height	50"	50"	50"
landing gear	fixed, tricycle	fixed, tricycle	fixed, tricycle
DESIGN WEIGHTS & LOADING			
maximum gross weight	3000 lbs	3000 lbs	3400 lbs
standard empty weight	2050 lbs	2070 lbs	2250 lbs
maximum load	950 lbs	930 lbs	1150 lbs
usable fuel capacity	56 gals / 336 lbs	56 gals / 336 lbs	81 gals / 486 lbs

🕅 CIRRUS

FACTORY OPTIONS

Enhance your CIRRUS aircraft with advanced options.


ICE PROTECTION



The TKS-based ice protection system pumps an antifreeze solution to the leading edges of the wings, horizontal stabilizer and to the propeller. Only available on the SR22.

ENGINE MONITORING

The FlightMax[®] EX5000C Emax Engine Monitoring displays engine information, fuel flow and computes nautical miles per gallon, remaining fuel and more.



STORMSCOPE[®] and SKYWATCH[®]

The WX-500 Stormscope[®] allows you to view lightning strikes on your MFD. Skywatch[®] monitors the airspace around your aircraft for nearby transponder-equipped aircraft.

SERVICE CENTER OPTIONS

SEMI-PORTABLE OXYGEN

Capable of providing oxygen to 17,500 ft, this aluminum cylinder has a 22 cubic feet capacity. It is installed as an arm rest and fixed between the two rear seats with four outlets.

AIR CONDITIONING

Lightweight 12,000 BTU system, provides cold dry air with its dedicated blower even during ground operations. Approximate added weight is 60 pounds installed. A variable speed circulation blower and ergonomic intuitive controls provide the occupants with the highest level of comfort. Air conditioning is only available for the SR22.

INTERIOR, EXTERIOR OPTIONS

SRV EXTERIOR



sr20 EXTERIOR










SRV INTERIOR







standard gray

sr20 INTERIOR



dove gray & shadow gray leather




leather

shadow gray

leather

feather beige

leather



shadow trim



dove gray leather

feather beige

leather & fabric

shadow gray leather



shadow gray leather & fabric



dark gray fabric feather beige leather

beige fabric











This brochure is designed to provide you with a general introduction to CIRRUS Products. CIRRUS reserves the right to discontinue or change the features, designs, materials, color and other specifications and the prices of their products, and to either permanently or temporarily withdraw any such products from the market without incurring any liability to any purchaser or prospective purchaser. Actual weights, specifications, exterior/interior paint scheme and colors may vary slightly.

leather Visit cirrusdesign.com CIRRUS DESIGN CORPORATION 4515 Taylor Circle, Duluth, MN 55811 218.788.3900

dove gray