CIRRUS AIRCRAFT MODELS

OPTIONS & PRICING	WEIGHT	PRICE
SRV Cirrus Airframe Parachute System™ [CAPS]	BASE PF	STANDARD
TCM IO-360-ES, 200 hp		STANDARD
AVIONICS		
Primary Flight Display [PFD] EX3000C Multi-Function Display [MFD]		STANDARD STANDARD
GMA 340 Audio Panel		STANDARD
GNC 420 GPS/COM GTX 327 Transponder		STANDARD STANDARD
SRV OPTIONS		STANDARD
cross country package	10	\$16,500
style package	18 7	\$6,600 \$2,500
dual alternator system 3-blade propeller	23	\$2,500
front wheel fairing	3	\$1,610
SR20	BASE PF	RICE \$236,700
Cirrus Airframe Parachute System™ [CAPS]		STANDARD
TCM IO-360-ES, 200 hp AVIONICS		STANDARD
Primary Flight Display [PFD]		STANDARD
EX3000C Multi-Function Display [MFD]		STANDARD
GMA 34O Audio Panel GNS 430/250XL, Autopilot 55SR		STANDARD STANDARD
GTX 327 Transponder		STANDARD
SR20 OPTIONS		Å
EX5000C Multi-Function Display [MFD] GNS 430/420, Autopilot 55SR ²	1	\$2,995 \$4,415
GNS 430/430, Autopilot 55X ²		\$17,845
3-blade propeller leather interior	23 9	\$3,450 \$3,395
	_	
SR22-G2 Cirrus Airframe Parachute System™ [CAPS]	BASE PF	STANDARD
TCM IO-550-N, 310 hp, 6-point mount		STANDARD
AVIONICS		
Primary Flight Display [PFD] EX5000C Multi-Function Display [MFD]		STANDARD STANDARD
GMA 34O Audio Panel		STANDARD
GNS 430/420, Autopilot 55SR GTX 327 Transponder		STANDARD STANDARD
SR22-G2 OPTIONS		STANDARD
GNS 430/430, Autopilot 55X		\$13,890
ice protection ³ air conditioning ¹	30 60	\$19,950 \$23,500
Platinum engine	00	\$4,750
polished spinner		\$595
ADDITIONAL OPTIONS [available for all mo		A - · · -
SkyWatch [®] traffic information ⁴ WX-500 Stormscope ^{®4}	13 8	\$21,500 \$9,795
Emax [®] engine & fuel monitoring ⁴	7	\$5,985
semi-portable oxygen ¹	13	\$1,990
WARRANTY		¢4 005
extended third year extended third year including avionics		\$4,995 \$5,995

¹installed at CIRRUS factory. retro fit price will vary when installed at a Cirrus Authorized Service Center; ²from base aircraft; ³due to special production preparations, the ICE PROTECTION option to be determined upon submission of order; ⁴upgrade to EX5000C required

SPECIFICATIONS	SRV	SR20	SR22-G2 [™]
PERFORMANCE			
takeoff	1341 ft	1341 ft	1020 ft
takeoff [50' object]	1958 ft	1958 ft	1575 ft
climb rate	900 ft/min	900 ft/min	1400 ft/min
stall speed with flaps	54 KIAS	54 KIAS	59 KIAS
cruise speed [75 [®] power]	150 KTAS	156 KTAS	185 KTAS
cruise range w/reserve	634 nm	733 nm	700 nm
maximum range	865 nm	882 nm	over 1000 nm
landing ground roll	1014 ft	1014 ft	1140 ft
landing over 50' object	2040 ft	2040 ft	2325 ft
ENGINE			
manufacturer	Continental	Continental	Continental
model	IO-360-ES	IO-360-ES	IO-550-N
horsepower	200	200	310
PROPELLER			
diameter	76"	76"	78"
description	2 blade	2 blade	3 blade
speed	constant	constant	constant
SPECIFICATIONS			
length	26'	26'	26'
height	8' 6"	8' 6"	8' 7"
wingspan	35' 7"	35' 7"	38' 6"
wing area	135 sq ft	135 sq ft	144.9 sq ft
cabin length	130"	130"	130"
cabin width	49"	49"	49"
cabin height	50"	50"	50"
landing gear	fixed, tricycle	fixed, tricycle	fixed, tricycle
DESIGN WEIGHTS & L	OADING		
maximum gross wt.	3000 lbs	3000 lbs	3400 lbs
standard empty wt.	2050 lbs	2070 lbs	2250 lbs
useful load	950 lbs	930 lbs	1150 lbs
usable fuel capacity	56 gal/336 lbs	56 gal/336 lbs	81 gal/486 lbs
payload	614 lbs	594 lbs	664 lbs

CIRRUS AIRCRAFT FINANCE

As with any major purchase, it's easiest to think in terms of monthly expenditures when deciding to buy. Contact the finance professionals at Cirrus Finance to help determine which option is best for you.

Our finance options include: Up to 90% financing on loans Up to 20-year amortization Fixed rate, ARM's and balloon loans

Our knowledgeable Cirrus Finance staff can be reached at 218.788.3833 or e-mail finance@cirrusdesign.com.